



Features	MixPre-3	MixPre-6
Description	3 input, 5-track audio recorder, mixer and USB audio interface	6 input, 8-track audio recorder, mixer and USB audio interface
RECORDER		
Recording Media	SD, SDHC, SDXC	SD, SDHC, SDXC
Tracks	5 (3 channel + mix)	8 (6 channel + mix)
Max Sampling Rate	96kHz	192kHz
Max Bit Depth	24	24
Audio File Format	Wav Poly	Wav Poly
Metadata Editing	✓	✓
Playback Audio Scrub	1/8x to 16x (FFWD and REW)	1/8x to 16x (FFWD and REW)
USB		
USB Ports	2 (1 USB-A, 1 USB-C)	2 (1 USB-A, 1 USB-C)
USB Audio Streaming	5 in to/ 2 out from Mac &/or Windows with ASIO driver 2 in to/ 2 out from Windows w/o ASIO driver	8 in to/ 4 out from Mac &/or Windows with ASIO driver 2 in to/ 2 out from Windows w/o ASIO driver
MIXER		
Simultaneous Recording, Mixing, USB audio streaming	✓	✓
Balanced Mic/Line Inputs	3 XLR	4 XLR/TRS combo

MIXER	MixPre-3	MixPre-6
Aux/Mic In (3.5 mm)		
4 uses: Camera Return, Plug-in-Power Mic, 2 ch Line In & Timecode	✓	✓
48V Phantom	✓	✓
Low Cut filters	40 - 160 Hz, 18dB/oct	40 - 160 Hz, 18dB/oct
Input Limiters	Analog	Analog
Output Limiters	Digital	Digital
Input Pair Linking (Stereo and M/S)	Pair 1-2	Pairs 1-2, 3-4, 5-6
Input Delay	--	✓
Input Polarity Reverse	--	✓
Input Gain, Pan, and Fader Controls	✓	✓
Input SOLOs (Individual or Multiple)	✓	✓
Unbalanced Stereo Output (3.5 mm) w/routing matrix	✓	✓
Headphone Output (3.5 mm; wide bandwidth, high gain)	✓	✓
User-Programmable Headphone Presets	✓	✓
LCD Metering	3 meter views	3 meter views
Multi-Color Ring LED Metering Surrounding Fader Knobs	✓	✓
Tone Generator	✓	✓
CONTROL INTERFACE		
Touchscreen, Sunlight-Readable	✓	✓
Ergonomic Channel Knobs	✓	✓
Backlit Transport Buttons	✓	✓
Operation Modes: Basic, Advanced, Custom	✓	✓
Load/Save User Setup	4 internal, unlimited to SD card	4 internal, unlimited to SD card
Multi-function Star Button	--	✓

TIMECODE	MixPre-3	MixPre-6
Reader	Time of Day, HDMI or LTC via Aux In	Time of Day, HDMI or LTC via Aux In
POWERING		
Power Source	4x AA or 8x AA, L-mount, USB-C	4x AA or 8x AA, L-mount, USB-C
REMOTE CONTROL		
Wingman iOS and Android app	✓ (via integrated Bluetooth Smart)	✓ (via integrated Bluetooth Smart)
Record Start/Stop Trigger	✓ (HDMI Flag or Timecode)	✓ (HDMI Flag or Timecode)
PHYSICAL		
Die Cast Aluminium Chassis	✓	✓
1/4" 20 mounting	✓	✓
Size	5.68" x 4.35" x 1.40" (144mm x 110mm x 36mm)	6.53" x 4.65" x 1.40" (166mm x 118mm x 36mm)
Weight	16.8 oz (.48 kg)	19.9 oz (.56 kg)
INCLUDED ACCESSORIES		
MX-4AA Battery Sled	✓	✓
Y-Cable (1 USB-C to 2 USB-A)	✓	✓
OPTIONAL ACCESSORIES		
MX-8AA Battery Sled	✓	✓
MX-Lmount Battery Sled (Li-Ion)	✓	✓
MX-Charge (Wall PSU w/USB-C)	✓	✓

